

# Discoverer AT3-LT tire specifications table

Tire Size	Service Description	UTQG	Load Range	Sidewall	Approved Rim Width	Measured Rim Width	Section Width	Overall Diameter	Tire Weight	Max Load	Tread Depth
LT215/85R16	115\112R		E	BLK	5.5 - 7	6	8.4	30.31	38	2680	16.5
LT235/85R16	120\116R		E	BLK	6 - 7.5	6.5	9.4	31.77	43	3042	16.5
LT225/75 R16	115\112R		E	BLK	6 - 7	6	8.5	29.33	39	2680	16.5
LT245/75 R16	120\116R		E	OWL	6.5 - 8	7	9.7	30.35	44	3042	16.5
LT265/75 R16	123\120R		E	OWL	7 - 8	7.5	10.6	31.61	50	3415	16.5
LT265/75 R16	112\109R		C	OWL	7 - 8	7.5	10.5	31.61	47	2470	16.5
LT245/70 R16	118\115R		E	OWL	6.5 - 7	7	9.8	29.53	43	2910	16.5
LT265/70 R16	121\118R		E	OWL	7 - 8.5	8	10.9	30.63	47	3195	16.5
LT235/80 R17	120\117R		E	OWL	6 - 7.5	6.5	9.2	31.77	43	3085	16.5
LT225/75 R17	116\113R		E	BLK	6 - 7.5	6	8.7	30.35	41	2755	16.5
LT245/75 R17	121\118S		E	OWL	6.5 - 7.5	7	10	31.5	47	3195	16
LT245/70 R17	119\116S		E	OWL	6.5 - 8	7	9.8	30.55	45	3000	16.5
LT265/70 R17	121\118S		E	OWL	7 - 8.5	8	10.9	31.65	50	3195	16.5
LT265/70 R17	112\109S		C	OWL	7 - 8.5	8	10.6	31.57	47	2470	16.5
LT275/70 R17	121\118R		E	OWL	7 - 8.5	8	11	32.17	52	3195	16.5
LT265/65 R17	120\117R		E	OWL	7 - 9.5	8	10.7	30.51	47	3085	16
LT275/65 R17	121\118S		E	OWL	7 - 9.5	8	11	31.1	50	3195	16
LT285/65 R17	121\118S		E	OWL	8 - 10	8.5	11.5	31.57	52	3195	16
LT265/65 R18	122\119R		E	BLK	7.5 - 9.5	8	10.7	31.54	48	3305	16
LT275/65 R18	123\120S		E	OWL	7.5 - 9	8	11.1	32.09	54	3415	16
LT265/60 R18	119\116S		E	BLK	7.5 - 9.5	8	10.7	30.51	49	3000	16